

STANDALONE Water Dispenser

EL-1407R/B



- Ultra safe & reliable water quality
- Stylish & attractive design-appearance
- Bacteria-resistance plastic used
- Stainless steel for cold and hot tank
- Adjustable temperature control through thermostat
- High efficiency compressor cooling
- Double safety protection against low water level
- Large storage cabinet
- POU water dispenser

Filter (RO system)	PP-GAC-CTO-RO-T33
Description	Hot & Cold: Compressor cooling with storage cabinet
Rated voltage/frequency	220-240V/110-127v
Hot tank capacity	0.96L
Heating power	550W
Heating capacity	5L/H,85-95°C
Cold tank capacity	3.4L
Cooling power	90W
Cooling capacity	2L/H, 5-10°C
Pure Water flow rate	7.8L/H
Total purified water	2000L
Dimension	310*400*1100mm

EL-1406R/B

- Ultra safe & reliable water quality
- Stylish & attractive design-appearance
- Bacteria-resistance plastic used
- Stainless steel for cold and hot tank
- Adjustable temperature control through thermostat
- High efficiency compressor cooling
- Double safety protection against low water level
- Large storage cabinet
- POU water dispenser

Filter (RO system)	PP-GAC-CTO-RO-T33
Description	Hot & Cold: Compressor cooling with storage cabinet
Rated voltage/frequency	220-240V/110-127v
Hot tank capacity	0.96L
Heating power	550W
Heating capacity	5L/H,85-95°C
Cold tank capacity	3.4L
Cooling power	90W
Cooling capacity	2L/H, 5-10°C
Pure Water flow rate	7.8L/H
Total purified water	2000L
Dimension	310*400*1100mm



2019 WATERWORLDUSA Inc.

COUNTERTOP Water Dispenser

EL-1506TF




- Ultra safe & reliable water quality
- Stylish & attractive design-appearance
- Bacteria-resistance plastic used
- Stainless steel for cold and hot tank
- Adjustable temperature control through thermostat
- High efficiency compressor cooling
- Double safety protection against low water level
- Large storage cabinet
- POU water dispenser

Filter (RO system)	PP-GAC-CTO-RO-T33
Description	Hot & Cold: Compressor cooling with storage cabinet
Rated voltage/frequency	220-240V/110-127v
Hot tank capacity	0.96L
Heating power	550W
Heating capacity	5L/H,85-95°C
Cold tank capacity	3.2L
Cooling power	90W
Cooling capacity	2L/H, 5-10°C
Pure Water flow rate	7.8L/H
Total purified water	2000L
Dimension	310*420*490mm

EL-1507TF

- Ultra safe & reliable water quality
- Stylish & attractive design-appearance
- Bacteria-resistance plastic used
- Stainless steel for cold and hot tank
- Adjustable temperature control through thermostat
- High efficiency compressor cooling
- Double safety protection against low water level
- Large storage cabinet
- POU water dispenser

Filter (RO system)	PP-GAC-CTO-RO-T33
Description	Hot & Cold: Compressor cooling with storage cabinet
Rated voltage/frequency	220-240V/110-127v
Hot tank capacity	0.96L
Heating power	550W
Heating capacity	5L/H,85-95°C
Cold tank capacity	3.2L
Cooling power	90W
Cooling capacity	2L/H, 5-10°C
Pure Water flow rate	7.8L/H
Total purified water	2000L
Dimension	310*420*490mm



2019 WATERWORLDUSA Inc.

More Product



[LM-YL1-208B](#)



[LM-YL1-208B](#)



[CHP-3850F](#)



[CHP-3971D](#)



[QZ-RY-101](#)

2019 WATERWORLDUSA Inc.