

Débit mètre-LZN-LZM

WWM FLOW METER-LZN-LZM

Model : LZN

Item no.	Débit		Matériel- Floater	In/Out Port
	GPM	LPM		
LZN-15G011	0.1-1	0.4-8	#316 SS	G 1/2"
LZN-15G022	0.2-2	1-7	#316 SS	G 1/2"
LZN-15G055	0.5-5	1.8-18	#316 SS	G 1/2"
LZN-20G110	1-10	4-36	#316 SS	G 3/4"
LZN-25G220	2-20	10-70	#316 SS	G 1"
LZN-25G330	5-30	20-100	#316 SS	G 1"
LZN-40G2060	20-60	80-220	#316 SS	G 1. 1/2"
LZN-50G2080	20-80	80-300	#316 SS	G 2"
LZN-50G20100	20-100	80-400	#316 SS	G 2"
LZN-50G40120	40-120	150-450	#316 SS	G 2"
LZN-50G40150	40-150	150-600	#316 SS	G 2"
LZN-50G50150	50-150	190-600	#316 SS	G 2"

Caractéristiques Techniques :

Précision : +4%
Matériel : Perspex
Température Max : 50 °C

Max Pression : 120Psi - (8.4 bar)
Débit : 0.1-150GPM (0.4-600LPM)



Model : LZM

Item no.	Débit		Matériel- Floater	In/Out Port
	GPM	LPM		
LZM-15011	0.1-1	0.4-8	#316 SS	G 1/2"
LZM-15022	0.2-2	0.8-8	#316 SS	G 1/2"
LZM-15055	0.5-5	2-18	#316 SS	G 1/2"
LZM-15110	1-10	4-8	#316 SS	G 1/2"
LZM-20210	2-10	8-40	#316 SS	G 3/4"
LZM-15214	2-14	8-50	#316 SS	G 1/2"
LZM-20216	2-16	8-60	#316 SS	G 3/4"
LZM-15220	2-20	8-8	#316 SS	G 1/2"
LZM-25424	4-24	10-100	#316 SS	G 1"
LZM-25535	5-35	10-130	#316 SS	G 1"
LZM-15540	5-40	10-150	#316 SS	G 1"
LZM-15545	5-45	10-180	#316 SS	G 1"

Caractéristiques Techniques :

Précision : +4%
Matériel : Perspex
Température Max : 50 °C

Max Pression : 120Psi - (8.4 bar)
Débit : 0.1-45GPM (0.4-180LPM)



2018 WaterworldUSA Inc.

